

DECLARATION OF PERFORMANCE

Nr. 01/2019 CERMED

1. Unique identification code of the product-type;
Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11 (4):
Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5 \%$, for internal and external walls and floorings
2. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: **internal and external walls and floorings**
3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11 (5):
Ceramica Mediterranea Spa – Zona Industriale 11/4 – 39011 Lana (BZ) – Italy
4. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 (2): not applicable
5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**
6. In case of the declaration of performance concerning a construction product covered by a harmonized standard: Name and number of notified body: not applicable
7. Declared Performance

1. A terméktípus egyedi azonosító kódja / *Unique identification code of the product-type:*

, anyagában színezett

2. Felhasználás célja(i) / *Intended use/es:* kül és beltéri felületek burkolása

3. Gyártó / *Manufacturer:* : Cermed Spa - S.S. 126 KM 95 - 09036 Guspini/CA-ITALIEN

4. A meghatalmazott képviselő / *Authorised representative:* Interplan srl. I-39011 Lana, Zona Industriale 11/4

5. Az AVCP-rendszer(ek) / *System/s of AVCP:* Rendszer 4.

6. Harmonizált szabvány / *Harmonised standard* : EN 14411 : 2016 szabvány szerint

7. A nyilatkozatban szereplő teljesítmény(ek) / *Declared performance/s:*

Essential Features	Performance	Harmonized technical specification
Reaction to fire	A1FL/A1	EN14411: 2016
Breaking strength	Thickness <7,5 mm effort ≥ 700 N Thickness $\geq 7,5$ mm effort ≥ 1300 N	
Modulus of Rupture	≥ 35 N/mm ²	
Scivolosita	See attached	
Tatilità	NPD	
Resistance to adhesion	NPD	
Durability External use Internal use	Passed Passed	
Resistance for temperature changes	Passed	
Release of dangerous substances, for:		
Release of lead Release of cadmium	<0,1 mg/dm ² <0,1 mg/dm ²	
Slipperiness	See table attached	

Slipperiness

Serie	Din 51130	PEI
30,2 x 60,4 DESIGN	R9	4
30,2 x 60,4 RAINBOW	R9	4
30,2 x 60,4 MARMETTE	R10	4
30,2 x 60,4 DETROIT	R9	4

8. The performance of the product identified in point 1 is in conformity with the declared performance in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.
9. Signe for and on behalf of the manufacturer by:

A fent azonosított termék teljesítménye megfelel a bejelentett teljesítmény(ek)nek. A 305/2011/EU rendeletnek megfelelően e teljesítménynyilatkozat kiadásáért kizárólag a fent meghatározott gyártó a felelős. / *The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.*

A gyártó nevében és részéről aláíró személy / *Signed for and on behalf of the manufacturer by:*

Lana, 07.06.2019

Ceramica Mediterranea S.p.a



Bernhard Mazohl
CERAMICA MEDITERRANEA S.p.A.
Stabilimento: Guspini
Uffici e Amministrazione:
Zona Industriale 11/4 - I-39011 LANA (BZ)
Tel 0473 55 97 54 - Fax 0473 56 51 82